


PATCHP24PHZF

24Port FTP Cat5e Patch Panel 19"



NOTES:

ELECTRICAL:

1. VOLTAGE RATING : 125 VAC RMS
2. CURRENT RATING : 1.5 AMP
3. CONTACT RESISTANCE : 100 MILLIOHMS MAX
4. INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 500 VDC
5. DIELECTRIC STRENGTH : 750 VAC RMS 60Hz,1MIN

ENVIRONMENTAL:

1. STORAGE : -40°TO +85°
2. OPERATION : 0° TO 70°

CONFORM TO TIA/EIA 568B CATEGORY 5e

MATES WITH MODULAR PLUG CONFORMING TO FCC PART 68,

MECHANICAL:

- 1.HOUSING MATERIAL: PBT+15%GF UL94V-0
- 2.PANEL FRAME : S45C, POWDER COATING IN BLACK COLOR
- 3.IDC MATERIAL : PC UL94V-0 TERMINAL:PHOSPHOR BRONZE,TIN PLATING
- 4.RJ45 JACK LIFE : 750 TIMES MIN
- 5.IDC LIFE : 200 TIMES MIN
- 6.WIRE : AWG 24~26
- 7.TIA Cat 5e Perm. Link Test: Worst pair NEXT margin \geq 5.0dB
- 8.Retentiveness of insertion structure: 50N 60 \pm 5s

CATEGORY 5e CHARACTERISTIC:

Frequence	Near-End Cross Talk dB, MIN.	Return Loss dB, MIN.	Attenuation dB, MAX.
1.0 MHZ	65.0	35.5	0.1
4.0 MHZ	65.0	35.5	0.1
8.0 MHZ	64.9	35.5	0.1
10.0 MHZ	63.0	35.5	0.1
16.0 MHZ	58.9	35.5	0.2
20.0 MHZ	57.0	34.0	0.2
25.0 MHZ	55.0	32.0	0.2
31.25 MHZ	53.1	30.1	0.2
62.5 MHZ	47.1	24.0	0.3
100.0 MHZ	43.0	20.0	0.4