


50 Port Telephone Patch Panel



NOTES:

ELECTRICAL:

- 1.VOLTAGE RATING : 125 VAC RMS
- 2.CURRENT RATING : 1.5 AMP
- 3.CONTACT RESISTANCE :100 MILLIOHMS MAX
- 4.INSULATION RESISTANCE :1000 MEGOHMS MIN @ 500 VDC
- 5.DIELECTRIC STRENGTH :750 VAC RMS 60Hz,1MIN

ENVIRONMENTAL:

- 1.STORAGE :-40° TO +85°
 - 2.OPERATION :0° TO 70°
- CONFORM TO ANSI/TIA/EIA 568B CATEGORY 3
MATES WITH MODULAR PLUG CONFORMING TO FCC PART 68

MECHANICAL:

1. HOUSING MATERIAL :PBT+15%GF UL94V-0
- 2.PANEL FRAME :CARBON STEEL,POWDER COATING IN BLACK COLOR
3. CONTACT MATERIAL :PC UL94V-0 CONTACT:PHOSPHOR BRONZE WITH NICKEL PLATING
4. RJ45 JACK LIFE :750 TIMES MIN
- 5.IDC LIFE :200 TIMES MIN
- 6.WIRE :AWG 24~26

PART NUMBER: PATCHP50P